

# ENHANCED MODULAR CONTROLLER SERIES MASTER



Starts at  
**\$499**



- Adds Multiple Protocol Conversion Functionality to Data Acquisition and Multi-Zone PID Control Applications
- Performs Hierarchical Control of Other Modules in the Modular Controller Series
- Stores Module Configuration Information, and Automatically Reprograms Replaced Modules
- Extensive Built-In Driver List Allows Easy Data Mapping to PLCs, PCs, and SCADA Systems
- Independent Serial Ports Provide Virtually Unlimited Integration Methods
- 10 Base-T/100 Base-TX Ethernet Connection Provides Networking Capability
- Supports up to 16 Modular Controller Series Modules
- Supports up to 9 Protocols Simultaneously (With Expansion Card)

The Model CSMSTRLE is a communications and control platform designed for use with Modular Controller Series slave modules. The CSMSTR uses a proprietary high speed serial protocol to communicate, via backplane connection, with up to 16 slave modules. Through the same connection, the Master also provides power to the modules.

When powered up, the CSMSTR automatically identifies and addresses connected slave modules. By storing the configuration information of all of the modules, the CSMSTR is able to automatically configure modules if they are replaced.

The Master provides high-speed RS232/422/485 communication ports and an Ethernet port for connection to PCs, PLCs, and SCADA systems. An extensive list of master and slave protocol drivers are available to allow the CSMSTR to share and exchange variable data with external devices. The 10 Base-T/100Base-TX Ethernet port can also be used to connect and share data with other devices at high speeds.

The design of the Modular Controller Series high density packaging and DIN rail mounting saves time and panel space. The controller snaps easily onto standard top hat (T) profile DIN rail.

The CSMSTR is programmed with Crimson 2.0 software for Windows® 2000 or later platforms. The software is an easy to use, graphical interface which provides a means of communication configuration, as well as commissioning and calibration of new systems.

## SPECIFICATIONS

**Power:** 24 Vdc  $\pm$  10% 400 mA min. (1 module)  
3.5A max. (16 modules + expansion Card)  
must use class 2 or SELV rated power supply.



CSMSTRLE, \$499, shown smaller than actual size.

## Communications:

**USB/PG Port:** Adheres to USB specification 1.1. Device only using Type B connection

**Serial Ports:** Format and Baud Rates for each port are individually software programmable up to 115,200 baud.

**RS232/PG Port:** RS232 port via RJ12

**COMMS Ports:** RS422/485 port via RJ45, and RS232 port via RJ12

**DH485 TXEN:** Transmit enable; open collector, VOH = 15 VDC, VOL = 0.5 V @ 25 mA max.

**Ethernet Port:** 10 BASE-T / 100 BASE-TX RJ45 jack is wired as a NIC (Network Interface Card)

## LEDs:

**STS:** Status LED indicates condition of master.

**TX/RX:** Transmit/Receive LEDs show serial activity.

**Ethernet:** Link and activity LEDs.

**CF:** Compactflash LED indicates card status and read/write activity

## Memory:

**On-Board User Memory:** 4 Mbytes of non-volatile flash memory

**On-Board SDRAM:** 2 Mbytes

**Memory Card:** Compactflash type II slot for type I and type II cards (Used for optional database storage only)

**Real Time Clock:** Typical accuracy is less than one minute per month drift

**Battery:** Lithium coin cell (included). Typical lifetime of 10 years at 25 °C (77°F)



**Environmental Conditions:**

**Operating Temperature Range:**  
0 to 50°C (32 to 122°F)

**Storage Temperature Range:**  
-30 to +70°C (-22 to 158°C)

**Operating and Storage Humidity:**  
80% max relative humidity, non-condensing, from 0 to 50°C (32 to 122°F)

**Vibration According to IEC 68-2-6:**  
5 to 150 Hz, in X, Y, Z direction for 1.5 hours, 2 g's

**Shock According to IEC 68-2-27:**  
Operational 25g, 11ms in 3 directions.

**Altitude:** Up to 2000 meters

**Construction:** Case body is burgundy high impact plastic and stainless steel. Installation category I, pollution degree 2

**Power Connection:** Removable wire clamp screw terminal block

**Wire Gage Capacity:** 24 AWG to 12 AWG  
**Torque:** 4.45 to 5.34 in/lb (0.5 to 0.6 N-m)

**Mounting:** Snaps onto standard DIN style top hat (T) profile mounting rails according to EN50022 -35 x 7.5 and -35 x 15

**Certification and Compliances:**

**Safety:**

UL Listed: File #E302106, UL508, CSA 22.2 No. 14-M05 LISTED by Und. Lab. Inc. to U.S. and Canadian safety standards IEC 61010-1, EN 61010-1: Safety requirements for electrical equipment for measurement, control, and laboratory use, Part 1

**Electromagnetic Compatibility:**

**Emissions and Immunity to EN 61326:** Electrical equipment for measurement, control and laboratory use

**Immunity to Industrial Locations\*:**

Electrostatic discharge EN 61000-4-2 Criterion A 2  
4 kV contact discharge  
8 kV air discharge  
Electromagnetic RF fields EN 61000-4-3 Criterion A 10 V/m  
Fast transients (burst) EN 61000-4-4 Criterion A  
2 kV power  
2 kV signal  
Surge EN 61000-4-5 Criterion A  
1kV L-L, 2 kV L&N-E power  
RF conducted interference EN 61000-4-6 Criterion A  
3 V/rms

**Emissions:**

Emissions EN 55011 Class A

**Weight:** 456.4 g (15.1 oz)

**\*Notes:**

1. Criterion A: Normal operation within specified limits.
2. This device was designed for installation in an enclosure. To avoid electrostatic discharge to the unit in environments with static levels above 4 kV, precautions should be taken when the device is mounted outside an enclosure. When working in an enclosure (ex. making adjustments, setting jumpers etc.), typical anti-static precautions should be observed before touching the unit.

**To Order (Specify Model Number)**

**MOST POPULAR MODELS HIGHLIGHTED!**

| MODEL NO.       | PRICE        | MASTER MODULE DESCRIPTION  |
|-----------------|--------------|--|
| <b>CSMSTRLE</b> | <b>\$499</b> | Modular controller master, multiple protocol converter (only)              |
| <b>SFCRM2MC</b> | <b>62</b>    | Modular controller crimson programming software, manual and download cable |
| ACCESSORIES     |              |  |
| MODEL NO.       | PRICE        | DESCRIPTION  |
| <b>G3CF064M</b> | <b>\$90</b>  | 64 MB compact flash card (industrial grade 2 million write cycles)         |
| <b>G3CF256M</b> | <b>235</b>   | 256 MB compact flash card (industrial grade 2 million write cycles)        |
| <b>G3CF512M</b> | <b>368</b>   | 512 MB compact flash card (industrial grade 2 million write cycles)        |
| <b>CBLPROG0</b> | <b>41</b>    | Programming cable for CS, G3, and paradigm                                 |
| <b>CBLUSB00</b> | <b>26</b>    | USB programming cable for G3, DSP and modular controller, type A-B         |
| <b>PSDR0100</b> | <b>129</b>   | Mini power supply 1A   |
| <b>PSDR0200</b> | <b>159</b>   | Mini power supply 2A   |
| <b>PSDR0400</b> | <b>199</b>   | Mini power supply 4A   |
| <b>RSRSTP00</b> | <b>5</b>     | Rail stops (qty 2)   |
| <b>CSTERM00</b> | <b>10</b>    | Replacement termination plug   |
| <b>CSBASE00</b> | <b>31</b>    | Replacement base   |
| <b>CSTERM00</b> | <b>10</b>    | Replacement termination plug   |
| MODULES         |              |  |
| MODEL NO.       | PRICE        | MODULE DESCRIPTION   |
| <b>CSDIO14R</b> | <b>\$247</b> | 8-inputs 6 relay outputs   |
| <b>CSDIO14S</b> | <b>247</b>   | 8-inputs 6 solid state outputs   |
| <b>CSINV800</b> | <b>536</b>   | 8-channel ±10 V input module   |
| <b>CSINI800</b> | <b>536</b>   | 8-channel 0(4) to 20 mA input module                                       |
| <b>CSOUT400</b> | <b>280</b>   | 4-channel analog output  |
| <b>CSPID1R0</b> | <b>227</b>   | Single loop module, relay outputs  |
| <b>CSPID1RA</b> | <b>247</b>   | Single loop module, relay outputs, analog output                           |
| <b>CSPID1RM</b> | <b>247</b>   | Single loop module, relay outputs, heater current input                    |
| <b>CSPID1S0</b> | <b>227</b>   | Single loop module, solid state outputs                                    |
| <b>CSPID1SA</b> | <b>247</b>   | Single loop module, solid state out. Analog output                         |
| <b>CSPID1SM</b> | <b>247</b>   | Single loop module, solid state, heater current input                      |
| <b>CSPID1TA</b> | <b>247</b>   | Single loop module, triac outputs, analog output                           |
| <b>CSPID2R0</b> | <b>340</b>   | Dual loop module, relay outputs  |
| <b>CSPID2RM</b> | <b>371</b>   | Dual loop module, relay outputs, heater current input                      |
| <b>CSPID2S0</b> | <b>340</b>   | Dual loop module, solid state outputs                                      |
| <b>CSPID2SM</b> | <b>371</b>   | Dual loop module, solid state outputs, heater current input                |
| <b>CSPID2T0</b> | <b>340</b>   | Dual loop module, triac outputs  |
| <b>CSPID2TM</b> | <b>371</b>   | Dual loop module, triac outputs, heater current input                      |
| <b>CSRTD600</b> | <b>402</b>   | 6-channel input, RTD   |
| <b>CSSG10RA</b> | <b>320</b>   | Single loop, 1 strain gage input, relay outputs, analog out                |
| <b>CSSG10SA</b> | <b>320</b>   | Single loop, 1 strain gage input, solid state out, analog out              |
| <b>CSSG11RA</b> | <b>400</b>   | Single loop, 2 strain gage input, relay outputs, analog out                |
| <b>CSSG11SA</b> | <b>400</b>   | Single loop, 2 strain gage input, solid state out, analog out              |
| <b>CSTC8000</b> | <b>536</b>   | 8-channel thermocouple module  |

Controllers come with termination plug, terminal power block, and complete operator's manual.  
**Ordering Example:** CSMSTRLE, controller, SFCRM2MC, software, G3CF512M, 512 MB flash card, CSDIO14R, 8 inputs 6 relay output module, PSDR0100, power supply, \$499 + 99 + 368 + 247 + 129 = **\$1342.**



#### UNITED STATES

[www.omega.com](http://www.omega.com)  
1-800-TC-OMEGA  
Stamford, CT.

#### CANADA

[www.omega.ca](http://www.omega.ca)  
Laval(Quebec)  
1-800-TC-OMEGA

#### GERMANY

[www.omega.de](http://www.omega.de)  
Deckenpfronn, Germany  
0800-8266342

#### UNITED KINGDOM

[www.omega.co.uk](http://www.omega.co.uk)  
Manchester, England  
0800-488-488

#### FRANCE

[www.omega.fr](http://www.omega.fr)  
Guyancourt, France  
088-466-342

#### CZECH REPUBLIC

[www.omegaeng.cz](http://www.omegaeng.cz)  
Karviná, Czech Republic  
596-311-899

#### BENELUX

[www.omega.nl](http://www.omega.nl)  
Amstelveen, NL  
0800-099-33-44



## More than 100,000 Products Available!

### • Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Glass Bulb Thermometers, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders Relative Humidity Measurement Instruments, RTD Probes, Elements and Assemblies, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples Thermowells and Head and Well Assemblies, Transmitters, Wire

### • Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

### • pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

### • Data Acquisition

Auto-Dialers and Alarm Monitoring Systems, Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485 and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

### • Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Strain Gages, Torque Transducers, Valves

### • Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters