

# LDM485

## Fully Isolated Limited Distance Modem, RS-232/422 Converter



- ✔ Complete Isolation with Optical Couplers and Power DC-to-DC Converter
- ✔ Industrial Surge Protection Devices
- ✔ Six LED Diagnostic Indicators
- ✔ 19.2K Baud at 3 Miles (5KM), 57.6K Baud at 0.5 Miles (0.8KM)
- ✔ Request-to-Send, Clear-to-Send Handshake
- ✔ Tri-State Outputs for Multidrop Applications, up to 64 Devices
- ✔ Selection of Connectors
- ✔ Wide Operating Temperature Range
- ✔ Solderless Screw Terminal Field Connections

The LDM485 is a compact RS-232 to RS-485 converter which features a complete electrical isolation barrier and heavy duty electrical surge protectors. These devices feature a rugged aluminum enclosure small enough to mount on the back panel of typical computer equipment, saving valuable desk and floor space. Isolation is provided by optical couplers and a DC-to-DC converter. The RS-232 connection is through male or female EIA 25-pin connectors. The RS-485 connections are made through convenient solderless screw terminals.

The LDM485 series is designed for full duplex operation over two-wire pairs. Outputs are tri-state, allowing multidropping of up to 64 units. Hardware handshake is available over two separate wire pairs. Data rates are DC to 57.6k baud. Six diagnostic LED indicators are provided (see Figure 1) for installation guidance and system troubleshooting. The RS-232



**\$287**  
Basic Unit

LDM485-P, \$287, shown smaller than actual size

interface supports Request To Send, Clear To Send, Data Set Ready, Received Line Signal Detect, and Data Terminal Ready. A convenient null modem switch is provided for the data lines. Also, a line termination switch connects a line termination resistor and line bias resistors to the RS-485 receive lines. The RS-485 interface supports Request To Send and Clear To Send on separate wire pairs. The LDM485 may be used to convert two sets of send and receive channels by using RTS and CTS circuits as the second data channels. Data rates are the same. The units use 12VAC from a wall-mounted transformer to screw terminals 1 and 2 on the RS-485 connector. Alternately, they can use  $\pm 12\text{VDC}$  to pins 9 (+) and 10 (-) of the RS-232 connector.

The LDM485 conforms to EIA RS-232 and RS-485 specifications. Data Terminal Ready must be asserted by the host RS-232 port

before the LDM485 can transmit data. When Data Terminal Ready is not asserted, all outputs of the LDM485 are high impedance, allowing up to 64 LDM485 units to be multidropped on a common communications cable. See Figures 1 and 3 for details.

Request To Send and Clear To Send are carried through the RS-485 port as two separate wire pairs. These may be used for full duplex flow control.

Data Terminal Ready, DTR, must be asserted before the LDM485 can transmit data. This is normally done by the host computer. For situations where the host equipment does not have the capability of supplying a DTR signal, RLSD may be used to automatically assert DTR. On the RS-232 connector P1 of each LDM485, simply connect RLSD pin 8 to DTR pin 20. This connection is not appropriate for multi-drop installations.

### SPECIFICATIONS

Model	LDM485					
<b>Baud Rate Range</b>	0 – 57.6K					
<b>Baud Rate</b>	57.6K	38.4K	19.2K	9.6K	4.8K	2.4K – 0
<b>Distance (miles)<sup>(1)</sup></b>	0.5	1	3	4	5	8
<b>Distance (km)</b>	0.8	1.7	5	6.7	8.3	13.3
<b>Wire Capacitance</b>	Equal to 25pF per foot and up to 32 multidrop units					
<b>Maximum Multidrop Units</b>	64					
<b>Common Mode Isolation</b>	Surge: 1500V Continuous: 1000V					
<b>Differential Mode Surge Protection (9 devices)</b>	(AC input) ANSI/IEEE C37.90.1-1989 (all RS-485 inputs and outputs)					
<b>Modes</b>	Asynchronous 4-wire duplex, 2-wire half-duplex, 2-wire simplex					

Notes: (1) Distances reduced if multidropping more than 32 units; by 30% for 33-48 units, 50% for 49-64.



RS-232 P1 Pin	Descriptions	RS-485 P2 Pin Descriptions
Pin 1	Case	Case Ground Pin 1
Pin 2	TD	12VAC Pin 2
Pin 3	RD	PWR RTN Pin 2
Pin 4	RTS	Receive Data Pin 3
Pin 5	CTS	RTS A Pin 3
Pin 6	DSR	Request To Send Pin 4
		RTS B Pin 4
Pin 7	Sig Gnd	Clear To Send Pin 5
Pin 8	RLSD	CTS A' Pin 5
Pin 9	+12VDC	CTS B' Pin 6
Pin 10	-12VDC	TD A Pin 7
Pin 16	Echo Sup	Terminal Ready Pin 8
		TD B Pin 8
Pin 17	Echo Sup	Signal Ground Pin 9
		SIG RTN Pin 9
Pin 20	DTR	Receive Line Signal Detect Pin 10
		RD A' Pin 10
		RD B' Pin 11
		SIG RTN Pin 12
		SIG RTN Pin 12
		Echo Suppression (tie to pin 17 to enable)
		Echo Suppression (tie to pin 16 to enable)
		Data Terminal Ready (connected to Data Set Ready)

Model	LDM485
Channel Lines <sup>(2)</sup>	TD, RD, RTS, CTS
Control Lines <sup>(2)</sup>	RTS, CTS, DTR, DSR, RLSD
Null Modem Switch	1 (Reverses RS-232 pins 2 and 3)
RS-485 Output Drive	60mA max/output
RS-485 Input Impedance	12kΩ min/input
Power:	
AC operation <sup>(3)</sup>	12VAC, ±10%, 10W screw terms 1 & 2
DC operation	+11.5 to +17VDC @ 500mA on pin 9 -11.5 to -17VDC @ 100mA on pin 10
Operating Environment	0°C to +70°C, 0-95% relative humidity, noncondensing
Dimensions	53.3 mmH x 167.6 mmW x 32.5 mmD (2.1 x 6.6 x 1.28")
Weight	200 g (7 oz) max
AC Transformer	311.8 g (11.0 oz) max
MTBF <sup>(4)</sup>	>100,000 hrs

Notes: (2) TD = Transmit Data, RD = Receive Data, RTS = Request To Send, CTS = Clear To Send, DTR = Data Terminal Ready, DSR = Data Set Ready, RLSD = Received Line Signal Detect. (3) 120VAC and 220 VAC power transformers are available. (4) Ground-benign environmental conditions (no salt atmosphere, <50°C ambient temperature).

### MOST POPULAR MODELS HIGHLIGHTED

To Order (Specify Model No.)			
Model No.	Price	RS232 Connector	Power Source
LDM485-P	\$287	25 Pin male	Host-powered
LDM485-S	287	25 Pin female	Host-powered
LDM485-PT	305	25 Pin male	Transformer
LDM485-ST	305	25 Pin female	Transformer

Includes operator's manual. Transformer powered units also include 120 Vac wall mount transformer.

Ordering Example: LDM485-ST converter: \$305.



#### UNITED STATES

[www.omega.com](http://www.omega.com)  
1-800-TC-OMEGA  
Stamford, CT.

#### CANADA

[www.omega.ca](http://www.omega.ca)  
Laval(Quebec)  
1-800-TC-OMEGA

#### GERMANY

[www.omega.de](http://www.omega.de)  
Deckenpfronn, Germany  
0800-8266342

#### UNITED KINGDOM

[www.omega.co.uk](http://www.omega.co.uk)  
Manchester, England  
0800-488-488

#### FRANCE

[www.omega.fr](http://www.omega.fr)  
Guyancourt, France  
088-466-342

#### CZECH REPUBLIC

[www.omegaeng.cz](http://www.omegaeng.cz)  
Karviná, Czech Republic  
596-311-899

#### BENELUX

[www.omega.nl](http://www.omega.nl)  
Amstelveen, NL  
0800-099-33-44



## More than 100,000 Products Available!

### • Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Glass Bulb Thermometers, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders Relative Humidity Measurement Instruments, RTD Probes, Elements and Assemblies, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples Thermowells and Head and Well Assemblies, Transmitters, Wire

### • Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

### • pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

### • Data Acquisition

Auto-Dialers and Alarm Monitoring Systems, Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485 and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

### • Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Strain Gages, Torque Transducers, Valves

### • Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters