

STRAIN AMPLIFIER/SIGNAL CONDITIONER MODULES FOR STRAIN GAGES, LOAD CELLS, AND TRANSDUCERS

DMD-460 Series

Starts at
\$390

Up to 2 kHz
Dynamic Response
DMD-465WB



DMD-465, \$390, shown smaller than actual size.

- ✓ Bridge Excitation
4 to 15 Vdc Up to 120 mA
- ✓ Works with 120, 350,
500 Ω and Greater
Bridge Circuits
- ✓ Adjustable Gain and Offset
- ✓ 6-Wire Bridge Connections
- ✓ Voltage and Current
Output Versions
- ✓ 115 and 230 Vac, and
DC-Powered Models

The DMD-460 Series bridge amplifiers are self-contained, AC- or DC-powered, signal conditioning modules for strain gages, load cells, and bridge-type sensors. The DMD-465 contains a precision differential instrumentation amplifier with voltage output. The similar DMD-465WB has a frequency response to 2 kHz, while the DMD-466 has a 4 to 20 mA output instead of a voltage output.

SPECIFICATIONS

Common

Power: Standard 115 Vac or optional 220 Vac $\pm 10\%$ 50/60 Hz or 10 to 36 Vdc 0.7 A @ 10V, 0.17 A @ 36V at maximum excitation load

Operating Temperature: 0 to 70°C (32 to 158°F)

Storage Temperature: -25 to 85°C (-13 to 185°F)

Weight: 510 g (18 oz)

Size: 96 L x 51 W x 73 mm H (3.75 x 2 x 2.87")

Bridge Supply

Excitation Voltage Range: 4 to 15 Vdc

Current Output: 120 mA max

Line and Load Regulation: (0 to 100 mA) 0.05% max

Output Noise: 0.5 mVrms

Voltage Output

DMD-465 and DMD-465WB

Gain Range: 40 to 250 (up to 1000 with external resistor on DMD-465 only)

Dynamic Response:

DMD-465: DC to -3 dB = 3 Hz

DMD-465WB: DC to -3 dB = 2 kHz

Max Output (2 k Ω Load): ± 10 Vdc

Output Impedance: 0.01 to 1 Ω

Output Offset: -5 to 2V
(DMD-465WB only)

Gain Temp Coefficient: 200 ppm/°C

Input Bias Current: 30 nA

Input Impedance: 3000 M Ω

Output Noise (RTO): @ gain = 100

DMD-465: 120 μ Vrms

DMD-465WB: 1 Hz to 2 kHz = 2 mV

Input Noise Line Frequency: 15 μ V p-p

Common-Mode Rejection: 90 dB @ gain 40, 100 dB @ gain 250

Common-Mode Input Voltage: ± 15 V

4 to 20 mA Transmitter DMD-466

Output: 4 to 20 mA, 0 to 20 mA

Input Range for 20 mA Output:

10 mV min, 50 mV max

Zero Adjust: 0 to ± 12 mA

Linearity: $\pm 0.05\%$ FS

Temperature Stability: 200 ppm/°C

Input Impedance: 1000 M Ω

Common-Mode Rejection: 90 dB

Common-Mode Input Voltage: ± 15 V

Compliance Voltage: 10 Vdc

Output Noise: 1 μ A rms @ gain

0.2 mA/mV, 1 to 100 Hz

Dynamic Response: DC to -3 dB = 3 Hz

Response Time: To 99% of final value

200 ms, typical; to 99.9% of final value

300 ms, typical

MOST POPULAR MODELS HIGHLIGHTED!

To Order (Specify Model Number)

MODEL NO.	PRICE	DESCRIPTION
DMD-465	\$390	Voltage output
DMD-465-220V	390	220 Vac powered DMD-465
DMD-465WB	390	High-frequency voltage output
DMD-465WB-220V	390	220 Vac powered DMD-465WB
DMD-466	390	Current output (4 to 20 mA)
DMD-466-220V	390	220 Vac powered DMD-466
DMD-466-DC	440	10 to 36 Vdc powered DMD-466
POWER CORD-SE	7	Power cord with stripped end termination

Comes complete with operator's manual.

Ordering Examples: DMD-465WB, wide bandwidth amplifier/signal conditioner module with 115 Vac power, \$390.

DMD-466, amplifier/signal conditioner module with 4 to 20 mA output, \$390.

Recommended Reference Book: The Industrial Electronics Handbook, EE-2454, \$190. See Section Y for Additional Books





UNITED STATES

www.omega.com
1-800-TC-OMEGA
Stamford, CT.

CANADA

www.omega.ca
Laval(Quebec)
1-800-TC-OMEGA

GERMANY

www.omega.de
Deckenpfronn, Germany
0800-8266342

UNITED KINGDOM

www.omega.co.uk
Manchester, England
0800-488-488

FRANCE

www.omega.fr
Guyancourt, France
088-466-342

CZECH REPUBLIC

www.omegaeng.cz
Karviná, Czech Republic
596-311-899

BENELUX

www.omega.nl
Amstelveen, NL
0800-099-33-44



More than 100,000 Products Available!

• Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Glass Bulb Thermometers, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders Relative Humidity Measurement Instruments, RTD Probes, Elements and Assemblies, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples Thermowells and Head and Well Assemblies, Transmitters, Wire

• Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

• pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

• Data Acquisition

Auto-Dialers and Alarm Monitoring Systems, Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485 and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Strain Gages, Torque Transducers, Valves

• Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters