


Lab Calibrator



CL3001, \$4495, shown smaller than actual size.

CL3001
\$4495



- ✓ 0.0025% Calibration Accuracy
- ✓ Source/Read Thermocouple, RTD, Voltage, Current and Pressure
- ✓ Custom RTD and SPRT Profiles
- ✓ RS232, USB and IEEE-488 Remote Control
- ✓ Isolated Measurement Channel
- ✓ Includes NIST Certificate with Calibration Data

The OMEGA® CL3001 calibrator is an accurate full-featured temperature, DC and pressure calibrator intended for R&D, manufacturing and calibration lab applications. The units simple design and ease of operation allow users to quickly familiarize themselves with its operations and features. Time saving functions like the ability to save, recall and automatically cycle through setpoints for each output range, the ability to enter user definable RTD curves, and a complete remote interface are several key features offered by the CL3001.

The CL3001 includes an isolated measurement channel consisting of two voltage ranges: 10V and 100V DC, milliAmp range 0 to 52 mA, milliAmp range. The isolated measurement includes 24 Vdc power, and accuracy of 0.005% of reading on voltage ranges. Measuring pressure with a PCL-PMA pressure module adaptor, the CL3001 will work with all OMEGA PCL-PM pressure modules. For information on these see specifications under PCL1200, please visit omega.com/pcl1200

Specifications

Accuracy: Stated in terms of absolute uncertainty for 1 year term. Thermocouple values include cold junction compensation. Values are best in given range and function. For breakdown of each range please refer to the manual omega.com/cl3001

Display: Primary input/output display and the isolated measurement channel display each have 2 line, 16 character fields

Temperature Units: User selectable, °F/°C

Communication: RS232, IEEE-488 (31 available addresses)

Operating Ambient: Less than 80% RH, 0 to 50°C (32 to 122°F), temperature Cal 18 to 28°C (64 to 82°F)

Power: 100V/120V or 220V/240V, ±10%, line frequency 47 to 63 Hz

Dimensions: 13.3 cm H (5.25") plus 2.9 cm (1.15") for extended feet width standard rack width 48.3 cm (19") 30.0 cm D (11.81") overall

Weight: 4 kg (9 lb)

Input/Output Functions: Include save, recall and automatically cycle through setpoints for each output range, the ability to enter user definable RTD curves, and remote interface command set.

Thermocouple Specification, Output/Input

Type	Range				Absolute Uncertainty [†]	
	°C		°F		°C	°F
K	-200	1372	-328	2502	0.16	0.29
J	-210	1200	-346	2192	0.16	0.29
T	-250	400	-418	752	0.14	0.25
E	-250	1000	1000	1832	0.15	0.27
N	-200	1300	-328	2372	0.18	0.32
L	-200	900	-328	1652	0.17	0.31
U	-200	600	-328	1112	0.56	1.01
XK	-200	800	-328	1472	0.13	0.23
R	0	1750	32	3182	0.33	0.59
S	0	1750	32	3182	0.36	0.65
B	600	1820	1112	3308	0.39	0.70
C	0	2316	324	201	0.26	0.47
BP	0	2500	324	532	0.32	0.58

[†] Values are best in range



DC Voltage Specifications, Output

Range	Absolute Uncertainty [†] ± (ppm of output μ V)		
	Ppm output	μ V	Resolution
0 to 100.000 mV	30	3	1 mV
0 to 1.00000V	30	10	10 μ V
0 to 10.0000V	30	100	100 μ V
0 to 100.000V	30	1 mV	1 mV

DC Voltage Specifications, Isolated Input

Range	Absolute Uncertainty [†] ± (ppm of reading mV)		
	Ppm rdg	mV	Resolution
0 to 10.0000V	50	0.2	100 μ V
0 to 100.000V	50	2.0	1 mV

DC Current Specifications, Output

Range	Absolute Uncertainty [†] ± (ppm of output μ A)		
	Ppm rdg	μ A	Resolution
0 to 100.000 mA	50	1	1 μ A

DC Current Specifications, Isolated Input

Range	Absolute Uncertainty [†] ± (ppm of reading μ A)		
	Ppm rdg	μ A	Resolution
0 to 50.000 mA	100	1	0.1 μ A

1. Loop power: 24V \pm 10%
 2. HART[®] resistor: 250 Ω \pm 3%
 3. Maximum rated loop current: 24 mA

Resistance Specifications, Output

Range	Absolute Uncertainty [†] ± Ohms		
	Ω	Resolution	Nominal Current
5 to 400.000 Ω	0.015	0.001 Ω	1 to 3 mA
5 to 4.00000 k Ω	0.25	0.01 Ω	0.1 to 1 mA

1. Continuously variable from 0 to 4 k Ω .
 2. For currents lower than shown, the specification becomes:
 New Spec. = Stated Spec. x Imin/Iactual.
 For example, a 500 μ A stimulus measuring 100 Ω has a specification of:
 0.015 Ω x 1 mA/500 μ A = 0.03 Ω .

[†] Values are best in range

Resistance Specifications, Input

Range	Absolute Uncertainty [†] ± (ppm of reading Ω)		
	Ppm rdg	Ω	Resolution
5 to 400.000 Ω	20	0.035	0.001 Ω
5 to 4.00000 k Ω	20	0.35	0.01 Ω

1. Loop power: 24V \pm 10%
 2. HART resistor: 250 Ω \pm 3%
 3. Maximum rated loop current: 24mA

RTD and Thermistor Specifications, Output

Type	Range				Absolute Uncertainty [†]	
	$^{\circ}$ C		$^{\circ}$ F		$^{\circ}$ C	$^{\circ}$ F
Pt 385, 100 Ω	-200	800	-328	1472	0.04	0.07
Pt 3926, 100 Ω	-200	630	-328	1166	0.04	0.07
Pt 3916, 100 Ω	-200	630	-328	1166	0.03	0.05
Pt 385, 200 Ω	-200	630	-328	1166	0.38	0.68
Pt 385, 500 Ω	-200	630	-328	1166	0.15	0.27
Pt 385, 1000 Ω	-200	630	-328	1166	0.07	0.13
Ni120, 120 Ω	-80	260	-112	500	0.02	0.04
Cu 427, 10 Ω	-100	260	-148	500	0.38	0.68
YSI 400	15	50	59	122	0.007	0.013

RTD and Thermistor Specifications, Input

Type	Range				Absolute Uncertainty [†]	
	$^{\circ}$ C		$^{\circ}$ F		$^{\circ}$ C	$^{\circ}$ F
Pt 385, 100 Ω	-200	800	-328	1472	0.012	0.07
Pt 3926, 100 Ω	-200	630	-328	1166	0.011	0.022
Pt 3916, 100 Ω	-200	630	-328	1166	0.006	0.011
Pt 385, 200 Ω	-200	630	-328	1166	0.009	0.016
Pt 385, 500 Ω	-200	630	-328	1166	0.008	0.014
Pt 385, 1000 Ω	-200	630	-328	1166	0.012	0.022
Ni120, 120 Ω	-80	260	-112	500	0.010	0.018
Cu 427, 10 Ω	-100	260	-148	500	0.069	0.124
YSI 400	15	50	59	122	0.007	0.013
SPRT	-200	660	-328	1220	0.06	0.011

[†] Values are best in range

AVAILABLE FOR FAST DELIVERY!

To Order (Specify Model Number)

Model No.	Price	Description
CL3001	\$4495	Precision lab calibrator

Comes complete with NIST certificate, operator's manual, power cord, and thermocouple shorting connector.

Ordering Example: CL3001, precision lab calibrator, \$4495.

Accessories

Model No.	Price	Description
PCL-PMA	\$310	Pressure module adaptor
CL-300-CABLE-(*)-2	10	Thermocouple extension cables
TAC-CAB	8	0.9 m (3') test leads
PCL422-TL	17	Stackable test leads

* Male mini-connector to spade lug, insert one thermocouple type J, K, T, E, R, S, B, N.



UNITED STATES

www.omega.com
1-800-TC-OMEGA
Stamford, CT.

CANADA

www.omega.ca
Laval(Quebec)
1-800-TC-OMEGA

GERMANY

www.omega.de
Deckenpfronn, Germany
0800-8266342

UNITED KINGDOM

www.omega.co.uk
Manchester, England
0800-488-488

FRANCE

www.omega.fr
Guyancourt, France
088-466-342

CZECH REPUBLIC

www.omegaeng.cz
Karviná, Czech Republic
596-311-899

BENELUX

www.omega.nl
Amstelveen, NL
0800-099-33-44



More than 100,000 Products Available!

• Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Glass Bulb Thermometers, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders Relative Humidity Measurement Instruments, RTD Probes, Elements and Assemblies, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples Thermowells and Head and Well Assemblies, Transmitters, Wire

• Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

• pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

• Data Acquisition

Auto-Dialers and Alarm Monitoring Systems, Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485 and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Strain Gages, Torque Transducers, Valves

• Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters