



¼ DIN Temperature Controllers

CN730 Series

\$108

All Models



- ✓ Dual Display
- ✓ Autotune
- ✓ RS485 Communications
- ✓ Free Software
- ✓ Alarm Functions
- ✓ Thermocouple/RTD Inputs
- ✓ Output Status

Panel punches available, visit omega.com/panelpunches



CN733, \$108, shown smaller than actual size.

The CN730 Series ¼ DIN temperature controllers offer easy-to-use programming menus designed for quick installation. Control functions include ON/OFF, PID, auto-tuning or manual tuning. The CN730 Series is available with relay, dc pulse or current output with two additional alarm outputs. The alarm outputs can be configured from 12 different preprogrammed settings. The CN730 Series accepts a variety of thermocouple and RTD inputs. Process value and set-point value are simultaneously displayed with the process value in red and setpoint in green.

Specifications

- Inputs:** Thermocouple or RTD, see chart
- Display:** Two 4-digit, 7-segment, LEDs
 - PV:** Red, 19 mm H (0.75")
 - SV:** Green, 12.7 mm H (0.5")
- Accuracy:** ±0.25% span, ±1 least significant digit
- Supply Voltage:** 100 to 240 Vac, 50/60 Hz
- Power Consumption:** 5 VA max
- Operating Temperature:** 0 to 50°C (32 to 122°F)
- Memory Backup:** Nonvolatile memory
- Control Output Ratings:**
 - Relay:** SPST, 5A @ 250 Vac resistive
 - Voltage Pulse:** 14V, 10 to -20% (max 40 mA)
 - Current:** 4 to 20 mA
- Communication:** RS485 MODBUS® communication protocol
- Panel Cutout:** ¼ DIN, 92 mm² (3.622 in²)
- Dimensions:** 96 x 96 x 15.8 mm bezel (3.78 x 3.78 x 0.625")
- Panel Depth:** 79.2 mm (3.125")
- Weight:** 425 g (15 oz)
- Front Panel Rating:** IP66

Input Types	Range
Pt100Ω RTD	0 to 100°C (32 to 212°F) -20 to 500°C (-4 to 932°F) -200 to 600°C (-328 to 1112°F)
Thermocouple Type B	100 to 1800°C (212 to 3272°F)
Thermocouple Type S	0 to 1700°C (32 to 3092°F)
Thermocouple Type R	0 to 1700°C (32 to 3092°F)
Thermocouple Type N	-200 to 1300°C (-328 to 2372°F)
Thermocouple Type E	0 to 600°C (32 to 1112°F)
Thermocouple Type T	-20 to 400°C (-4 to 752°F) -200 to 400°C (-328 to 752°F)
Thermocouple Type J	-20 to 400°C (-4 to 752°F) -100 to 850°C (-148 to 1562°F)
Thermocouple Type K	-200 to 1300°C (-328 to 2372°F) -200 to 500°C (-328 to 932°F)
Thermocouple Type L	-200 to 500°C (-328 to 932°F)
Thermocouple Type U	-200 to 800°C (-328 to 1472°F)

IN STOCK FOR FAST DELIVERY!

To Order (Specify Model Number)		
Model No.	Price	Description
CN733	\$108	Relay output, with RS485 communications*
CN732	108	DC pulse output, with RS485 communications*
CN735	108	4 to 20 mA output, with RS485 communications*

* Free CN7-A software download available on omega.com/cn730

Accessories (Field Installable)

Model No.	Price	Description
CNQUENCHARC	\$8	Noise suppression RC snubber (2 leads), 110 to 230 Vac
CN7-485-USB-1	99	RS485 to USB mini-node converter

Comes complete with operator's manual.
Ordering Example: CN733, single output controller, mechanical relay, RS485 communications, \$108.





UNITED STATES

www.omega.com
1-800-TC-OMEGA
Stamford, CT.

CANADA

www.omega.ca
Laval(Quebec)
1-800-TC-OMEGA

GERMANY

www.omega.de
Deckenpfronn, Germany
0800-8266342

UNITED KINGDOM

www.omega.co.uk
Manchester, England
0800-488-488

FRANCE

www.omega.fr
Guyancourt, France
088-466-342

CZECH REPUBLIC

www.omegaeng.cz
Karviná, Czech Republic
596-311-899

BENELUX

www.omega.nl
Amstelveen, NL
0800-099-33-44



More than 100,000 Products Available!

• Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Glass Bulb Thermometers, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders Relative Humidity Measurement Instruments, RTD Probes, Elements and Assemblies, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples Thermowells and Head and Well Assemblies, Transmitters, Wire

• Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

• pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

• Data Acquisition

Auto-Dialers and Alarm Monitoring Systems, Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485 and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Strain Gages, Torque Transducers, Valves

• Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters