



One Omega Drive
Stamford, CT 06907-0047
omega.com
e-mail: info@omega.com

MSDS-0136
OB-300
Rev. Date 01/29/07
Supersedes: 09/05

The information contained herein is based upon data considered true and accurate. However, OMEGA makes no warranties, express or implied, as to the accuracy or adequacy of the information contained herein or the results to be obtained from the use thereof. This information is offered solely for the user's consideration, investigation and verification. Since the use and conditions of use of this information and the material described herein are not within the control of OMEGA, OMEGA assumes no responsibility for injury to the user or third persons. The material described herein is sold only pursuant to OMEGA's Terms and Conditions of Sale, including those limiting warranties and remedies contained herein, it is the responsibility of the user to determine whether any use of this data and information is in accordance with applicable federal, state or local laws and regulations.

© Copyright 2008 OMEGA ENGINEERING, INC., ALL RIGHTS RESERVED



One Omega Drive
Stamford, CT 06907-0047
omega.com
e-mail: info@omega.com

MSDS-0136
OB-300
Rev. Date 01/29/07
Supersedes: 09/05

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: OMEGABOND® 300 Air Set Cement

SUPPLIER: OMEGA Engineering, Inc.
ADDRESS: PO Box 4047
Stamford, CT 06907

TELEPHONE: (203) 359-1660

ITEM NUMBER: OB-300
ITEM DESCRIPTION: OMEGABOND® 300 Adhesive Cement Powder
PRODUCT DESCRIPTION: High Temperature Bonding Mortar
CHEMICAL FAMILY: Sodium Silicate Cement; aNa₂O·bSiO₂
REVISION DATE: 01/29/07
PRODUCT USE: High temperature bonding/adhesive compounds

SECTION 2. COMPOSITION AND DATA ON COMPONENTS

COMPONENT	CAS #	ACGIH TLV	OSHA PEL	% WT
SODIUM SILICATE	1344-09-8	NE	NE	<40%
SILICA, CRYSTALLINE	14808-60-7	0.025 MG/M ³ TWA	0.1 MG/M ³ STEL	<90%

NOTES: Exposure values shown for guidance only. Please follow applicable regulations.

SECTION 3. HAZARDS IDENTIFICATION

HMIS rating

Health	1
Flammability	0
Reactivity	0
Personal protection	A

THRESHOLD LIMIT VALUE: SiO₂ - 0.1 mg/m³

EFFECTS OF OVEREXPOSURE: Since this product is a mixture, there is no exposure limit established for it. Hazardous components and their associated permissible exposure limits are listed in the section titled "Composition and Data on Components". Specific health hazards from the various ingredients include:

SILICOSIS: Repeated inhalation of respirable free silica dust may cause delayed lung injury. May cause skin irritation or burns to eyes, respiratory tract, and stomach.

INHALATION: Sneezing, burning, or itching in nose and throat

EYE: Pain, redness, and tearing

SKIN: Itching or burning

INGESTION: Burning of mouth, throat, and stomach



One Omega Drive
Stamford, CT 06907-0047
omega.com
e-mail: info@omega.com

MSDS-0136
OB-300
Rev. Date 01/29/07
Supersedes: 09/05

SECTION 4. FIRST AID MEASURES

EYE CONTACT: Flush eyes immediately with water or physiological saline for at least 15 minutes while lifting upper and lower lids. Seek medical attention.

INGESTION: If swallowed, do not induce vomiting. Give large quantities of water. Seek medical attention. Never give anything by mouth to an unconscious person.

INHALATION: If difficulty breathing, move to fresh air at once. Apply artificial respiration if breathing has stopped. Seek medical attention.

SKIN CONTACT: Wash contact area thoroughly with soap and water. Remove contaminated clothing. Launder before reuse. Seek medical attention if erythema develops.

SECTION 5. FIRE FIGHTING MEASURES

AUTO IGNITION TEMPERATURE: NA

EXPLOSION DATA - Not sensitive to mechanical impact or static discharge.

EXTINGUISHING MEDIA: NA

NOTE: Many dusts and aerosols may exhibit explosive characteristics if ignited by static discharge or spark. Exercise care to avoid causing dusting or misting.

FIRE AND EXPLOSION HAZARDS: NA

FIRE FIGHTING PROCEDURES: NA

FLAMMABILITY - Not flammable in presence of open flame, sparks, excessive heat and static discharge.

FLAMMABLE LIMITS LEL: NA

FLAMMABLE LIMITS UEL: NA

FLASHPOINT: NA

DOT LABEL: NONE

OTHER: NA



One Omega Drive
Stamford, CT 06907-0047
omega.com
e-mail: info@omega.com

MSDS-0136
OB-300
Rev. Date 01/29/07
Supersedes: 09/05

SECTION 15. REGULATORY INFORMATION (CONT'D)

CANADA

DSL: Components included on inventory.

WHMIS HAZARD CLASS (ES):

Class D, Division 2, Subdivision B: Materials cause other toxic effects, toxic material.

WHMIS TRADE SECRET REGISTRY NUMBER(S): Not Applicable

WHMIS SYMBOLS:

Stylized T

EUROPEAN ECONOMIC COMMUNITY (EEC)

EINECS Inventory: Components included on inventory

EEC SYMBOL(S):

Irritant

Harmful

EEC RISK[®] PHRASES: Irritating to eyes, respiratory system, and skin

HARMFUL: Danger of serious damage to health by prolonged exposure

EEC SAFETY PHRASES:

Do not breathe dust

Avoid contact with skin and eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

Wear suitable protective clothing, gloves, and eye and face protection

Keep container tightly closed and dry

SECTION 16. OTHER INFORMATION

This MSDS contains information and recommendations based upon our present knowledge and data believed to be reliable. All data shown here are subject to reasonable variation and are supplied as an accommodation to the buyer. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This MSDS applies only to the product in its "as manufactured" state, since the application to which the product is subjected may change its characteristics. The buyer is responsible for determining the safety, toxicity, and suitability of the product under the conditions of their use of the product. Buyers also have the responsibility for insuring that the MSDS is available to their employees, product users, and handlers.

NA = Not applicable **NE** = Not established **D** = Decomposes



One Omega Drive
Stamford, CT 06907-0047
omega.com
e-mail: info@omega.com

MSDS-0136
OB-300
Rev. Date 01/29/07
Supersedes: 09/05

SECTION 12. ECOLOGICAL INFORMATION

Crystalline silica (quartz) is not known to be an environmental hazard.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Sweep up excess; flush area with large quantities of water. Material could be disposed of in approved landfill according to Federal, state, and local regulations.

EUROPEAN COMMUNITY WASTE DISPOSAL KEY: Not known

UNCLEANED PACKAGINGS: Disposal must be made according to official regulations.

SECTION 14. TRANSPORT INFORMATION

DOT I.D. NO.:	NOT REGULATED
DOT SHIPPING NAME:	NA
DOT HAZARD CLASS:	NOT REGULATED
DOT LABEL:	NONE
OTHER:	NA
NMF CLASSIFICATION:	HIGH TEMPERATURE BONDING MORTAR

SECTION 15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

TSCA Status:

Components are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

SARA TITLE III:

Section 302 Extremely Hazardous Substances: None above detection limits.

Section 311/312 (40 CFR 370) Hazardous Categories:

Carcinogen

Irritant

There are no listed chemicals above detection limits in this compound.

CERCLA: None

STATE REGULATIONS:

California: proposition 65 substances (components) know to the State of California to cause cancer and reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Act of 1986".

It has not been determined and cannot be ascertained that this product would not expose users to the listed chemicals at the very low levels prescribed in the regulations. Therefore, it is the user's responsibility to determine if the percent of hazardous/carcinogenic ingredients listed



One Omega Drive
Stamford, CT 06907-0047
omega.com
e-mail: info@omega.com

MSDS-0136
OB-300
Rev. Date 01/29/07
Supersedes: 09/05

SECTION 6. ACCIDENTAL RELEASE MEASURES

CLEAN-UP PROCEDURE: Sweep, scoop, or vacuum the discharged material.

Respiratory protection should be worn at all times and skin contact should be avoided. Observe environmental regulations.

SECTION 7. HANDLING AND STORAGE

Avoid contact with eyes, skin, and clothing.

Avoid breathing dust.

For industrial use only!

Harmful if inhaled.

Do not take internally.

May cause irritation.

Wear chemical splash goggles, gloves, and protective clothing.

Use adequate ventilation and employ respiratory protection where dust may be generated.

Wash thoroughly after handling.

Store in a cool, dry place.

Keep container closed when not in use.

Always mix well before using.



One Omega Drive
Stamford, CT 06907-0047
omega.com
e-mail: info@omega.com

MSDS-0136
OB-300
Rev. Date 01/29/07
Supersedes: 09/05

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

See Section 2 for the components that have limit values that require monitoring at the workplace.*

* This product contains encapsulated silica. By OSHA letter of interpretation, the silica is not considered respirable in either the cement paste form or cured cement form. However, if the cured cement is polished, ground or chipped during the processing, handling or use, the silica maybe released as an airborne respirable particle. In these instances appropriate personal protection equipment and local ventilation controls must be employed.

EYE PROTECTION: Safety glasses with side shields, chemical-type goggles, or face shield. Contact lenses should not be worn.

RESPIRATORY PROTECTION: Any dust respirator for 5 times PEL or less. Any fume respirator or high efficiency particulate filter respirator for 10 times PEL or less. If TLV of any component is exceeded, use appropriate respiratory protection or ventilate in accordance with OSHA Regulation 29 CFR Part 1910.

SKIN PROTECTION: Suitable protective gloves (neoprene, butyl rubber, or viton). Clothing should be clean, long-sleeved work clothes. Wash thoroughly before eating, smoking, applying cosmetics, etc. Thoroughly launder work clothes before reuse. Safety shower nearby.

VENTILATION: Normal ventilation for good working conditions should be used.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

% VOLATILE BY VOLUME:	NA
APPEARANCE AND ODOR:	White powder; odorless.
BOILING POINT:	NA
COEFFICIENT OF WATER/OIL DISTRIBUTION:	Not available
EVAPORATION RATE:	NA
MELTING POINT:	NA
ODOR THRESHOLD:	Not available
PH:	NA
SPECIFIC GRAVITY:	8.75#/gallon
SOLUBILITY IN WATER:	<15%

SECTION 10. STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Avoid dampness, keep dry until used.

HAZARDOUS DECOMPOSITION PRODUCTS: None

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: NA

INCOMPATIBILITY: (Materials to avoid) None

STABILITY: Stable



One Omega Drive
Stamford, CT 06907-0047
omega.com
e-mail: info@omega.com

MSDS-0136
OB-300
Rev. Date 01/29/07
Supersedes: 09/05

SECTION 11. TOXICOLOGICAL INFORMATION

ACGIH NOT AVAILABLE

IARC YES

EFFECTS OF ACUTE EXPOSURE: Refer to Section 3.

EFFECTS OF CHRONIC EXPOSURE: Refer to Section 3.

MUTAGENIC EFFECTS: If not addressed in Section 3, the data is not available.

REPRODUCTIVE TOXICITY: If not addressed in Section 3, the data is not available.

TERATOGENIC EFFECTS: If not addressed in Section 3, the data is not available.

NAME(S) OF TOXICOLOGICALLY SYNERGISTIC PRODUCTS AND EFFECTS: If not addressed in Section 3, data is not available.

ADDITIONAL INFORMATION: Crystalline Silica (Quartz)

Silicosis - The major concern is silicosis caused by the inhalation of respirable crystalline silica dust. Silicosis can exist in several forms, chronic (or ordinary), accelerated, or acute.

Cancer - Silica is listed by IARC and NTP as having sufficient evidence to be a carcinogen in humans and in experimental animals for the carcinogenicity of quartz and cristobalite. The overall IARC evaluation was that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (group 1).

Scleroderma - There is evidence that exposure to respirable crystalline silica or silicosis is associated with incidence of scleroderma of the lungs.

Tuberculosis - Individuals with silicosis are at risk to develop Tuberculosis, if exposed to persons with tuberculosis.

Nephrotoxicity - Recent studies suggest that exposure to respirable crystalline silica or that the disease silicosis is associated with the increased incidence of kidney disorders.

LC50/LD50: There is no data available.

ADDITIONAL INFORMATION: The LD50 (oral, rat) for sodium silicate is reported to be in the range 1300-1600 mg/kg, depending on the ratio.

EYE IRRITANT:	Yes
INGESTION IRRITANT:	Yes
INHALATION IRRITANT:	Yes
RESPIRATORY SENSITIZER:	No
SKIN IRRITANT:	Yes